

**Material Safety Data Sheet**

may be used to comply with OSHA's standard  
Communication Standard, 29 CFR 1910.1200. Standard  
must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

**Section I**

Manufacturer's name	Earth Friendly Building Materials	Emergency Telephone Number	1-877-272-7872
Address (Number, Street, City, State and ZIP Code)		Telephone Number for Information	1-602-541-0791
	205 S Industrial Dr.	Date Prepared	Aug 3, 2004
	Tempe, AZ 85281	Signature of Preparer (optional)	

**Section II—Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Hydrated Portland Cement, Recycled Polystyrene				
No hazardous materials				
No volatiles				
Inert material				

**Section III—Physical/Chemical Characteristics**

Boiling Point	N/A	Specific Gravity (H <sub>2</sub> O = 1)	0.35
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Not Soluble		
Appearance and Odor	Grey - cementitious, odorless		

**Section IV—Fire and Explosion Hazard Data**

Flash Point (Method Used)	N/A	Flammable Limits	LEL	N/A	UEL	N/A
Extinguishing Media	N/A					
Special Fire Fighting Procedures	N/A					
Unusual Fire and Explosion Hazards	N/A					