



- ① FINISHED GRADE
- ② 18" MINIMUM BELOW FINISH GRADE
- ③ FOOTING SIZE PER DESIGN
- ④ OFFSET WIDEN FOOTING 4"
- ⑤ REINFORCING PER DESIGN
- ⑥ VERTICAL DOWELS TO MATCH ICF WALL VERTICAL REINFORCING ALTERNATE BENDS
- ⑦ #4 VERTICAL DOWELS AT 48" O.C. CENTER DOWELS IN SLAB THICKNESS AND PROVIDE 32" EMBEDMENT INTO SLAB
- ⑧ ICF TYPICAL HORIZONTAL REINFORCING
- ⑨ ICF TYPICAL VERTICAL REINFORCING
- ⑩ 4" THICK CONCRETE SLAB OVER 4" ABC FILL
- ⑪ OPTIONAL POUR JOINT
- ⑫ 9" MINIMUM FIRST POUR THICKNESS
- Ⓐ LAP REINFORCING BARS PER 40 DIAMETERS

NOTE:
 ICF SCREEN GRID TO BE PER IRC 2012 FOOTING WIDTH, REBAR SIZE AND SPACING PER SECTION R611 - 2012

11 ICF WALL AT CONTINUOUS FOOTING

SCALE: 1'-0" = 3/4"