

Material Safety Data Sheet

may be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name	Earth Friendly Building Materials	Emergency Telephone Number	1-877-272-7872
Address (Number, Street, City, State and ZIP Code)		Telephone Number for Information	1-602-541-0791
	205 S Industrial Dr.	Date Prepared	Aug 3, 2004
	Tempe, AZ 85281	Signature of Preparer (optional)	

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Hydrated Portland Cement, Recycled Polystyrene				
No hazardous materials				
No volatiles				
Inert material				

Section III—Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	0.35
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Not Soluble		
Appearance and Odor	Grey - cementitious, odorless		

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used)	N/A	Flammable Limits	LEL	N/A	UEL	N/A
Extinguishing Media	N/A					
Special Fire Fighting Procedures	N/A					
Unusual Fire and Explosion Hazards	N/A					

(Reproduce locally)

OSHA 174 Sept. 1985